

B-VENT PRODUCT DATA

DESCRIPTION

B-Vent

APPLICATIONS

- Category 1 Gas Burning Appliances
- Approved for Natural Gas (NG), Propane (LP)
- Typical Usage: Intended to be used for Furnaces, HWT, Boilers, Pool Heaters, Unit Heaters, Gas Fireplaces, Infrared Tube Heaters



FEATURES AND BENEFITS

- Diameter: 3" - 36" (insulated: 4" - 14")
- Minimum Clearance to Combustibles: 1"
- UL/ULC screws are not required to be used in B-Vent manufactured by Don Park because of Don Park's connection method. For Don Park B-Vent manufactured after March, 2007, screws are permitted to be installed at joints as an optional attachment method but are not mandatory. When using screws they are to be located approximately 1/4" from the connection joint using a maximum **1/4" long screws** so the screws do not pierce or deform the inner liner
- Warranty: 1 Year

PRODUCT DATA

- UL/ULC Listed Sizes 3" - 30" - ULC 32", 34" & 36"
- Maximum Temperature Rating: 243^oc or 470^oF
- Material: Outer Casing: Galvalume or Aluminized
Inner Liner: Aluminum
Outer Casing & Inner Liner separated by annular air space (1/2")
(except for 32", 34" & 36" diameters)
- Vent Diameter: 1" less than outside diameter (1/2" wall) except for 32", 34" & 36" which is 2" less (1" wall)