

# TAKE OFF AIRTIGHT

## DESCRIPTION

Airtight, easy install, round duct take off is available in various gauges of galvanized steel; with or without damper.

## APPLICATIONS

Cut into the plenum or rectangular duct. Used to begin pipe truckline and branchline runs. Side, top or bottom mount.

## FEATURES & BENEFITS

- Airtight design- includes double side 1/8" thick adhesive gasket on a circular perimeter flange to seal to the duct and special 3M pressure sensitive tape to seal the collar overlap
- Total height is under 3 1/2"
- Damper is positioned low in collar to allow air to be deflected into the take off
- Has a balanced damper assembly
- Collar is riveted together then is crimped and beaded
- Designed so the hole in the duct does not have to be perfect
- Low profile design for tight spaces
- Flange has 4 pre-punched screw holes to screw to duct face
- Saves installation time
- Union Made



## WITHOUT DAMPER

Part Number	Description	UOM	Ctn.Qty
4ATT004	4" AIRTIGHT TAKEOFF	EA	20
4ATT005	5" AIRTIGHT TAKEOFF	EA	18
4ATT006	6" AIRTIGHT TAKEOFF	EA	10
4ATT007	(M) 7" AIRTIGHT TAKEOFF	EA	3
4ATT008	8" AIRTIGHT TAKEOFF	EA	32

## WITH DAMPER

Part Number	Description	UOM	Ctn.Qty
4ATTOWD04	4" AIRTIGHT TAKEOFF W/DAMP	EA	20
4ATTOWD05	5" AIRTIGHT TAKEOFF W/DAMP	EA	42
4ATTOWD06	6" AIRTIGHT TAKEOFF W/DAMP	EA	21
4ATTOWD07	7" AIRTIGHT TAKEOFF W/DAMP	EA	9
4ATTOWD08	8" AIRTIGHT TAKEOFF W/DAMP	EA	32
4ATTOWD10	10" AIRTIGHT TAKEOFF W/DAMP	EA	22
4ATTOWD12	12" AIRTIGHT TAKEOFF W/DAMP	EA	15
4ATTOWD14	14" AIRTIGHT TAKEOFF W/DAMP	EA	4

## HEAD OFFICE

2259 Markham Road, Scarborough  
Ontario, Canada M1B 2W3  
TEL: 416.449.7275 FAX: 416.449.2614